

Fire Retardant Coatings of Texas®, LLC 1150 Blue Mound Rd West #403 • Haslet, Texas 76052 Office (817) 710-5233 Fax (817) 439-8385 www.frctexas.com



FX LumberGuard® XT

Certificate of Fire Retardant Wood Treatment

	Date of Service:
Batch Code or Order No.:	
	below was treated with FX Lumber Guard XT and has been
•	
	cation specifications, ICC-ESR-3872, ICC ESL-1087, ICC
ESL-1064, IAPMO UES ER-478 and Intert	tek CCRR-1044.
Your Invoice #	dated 20
Tour invoice #	dated 20
Description of material treated:	
Description of material freated.	
	Spread Rate: 300-350 square feet per gallon
Square Foot Treated:	
Square Foot Treated: Applicator:	Spread Rate: 300-350 square feet per gallon
Square Foot Treated: Applicator: Name:	Spread Rate: 300-350 square feet per gallon
Square Foot Treated: Applicator: Name:	Spread Rate: 300-350 square feet per gallon
Square Foot Treated: Applicator: Name: Address: City: ST: ZIP:	Spread Rate: 300-350 square feet per gallon
Square Foot Treated: Applicator: Name:	Spread Rate: 300-350 square feet per gallon

"Fire Retardant Coatings of Texas", "FX Lumber Guard / FX Lumber Guard XT" & "FRCT" Logo are federally registered trademarks of Fire Retardant Coatings of Texas, LLC